


YE24
EUROPE
2024 / 2025



CUTTING TOOLS



TOOLING SYSTEM

YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




TEST
BAR

TB

TEST BAR

KONTROLLDORN
MANDRIN DE CONTRÔLE
MANDRINO DI CONTROLLO
MANDRIL DE CONTROL



JIS
B6339-
BT







Unit : mm					
TAPER No.	MODEL No.	EDP No.	D	L	WEIGHT(Kg)
40	BT40-TB40-300	P2802305	40	300	4.59
50	BT50-TB50-300	P2802307	50	300	6.88

YG-1 TOOLING SYSTEM

HSK
(DIN 69893/ISO 12164)



HYDRAULIC CHUCK

SHRINK FIT HOLDER

ER COLLET CHUCK

END MILL HOLDER

SHELL MILL ARBOR

COMBI-SHELL MILL ARBOR

POWER MILLING CHUCK

MORSE TAPER ARBOR

SK SLIM CHUCK

SYNCHRO TAPPING CHUCK

ONE STEP TAPPING CHUCK

TAPPING ER CHUCK

TAPPING CHUCK

FACE MILL ARBOR

COPY MILL ARBOR

INDEXABLE DRILL HOLDER

NC DRILL CHUCK

BLANK BAR

TEST BAR

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS



HYDRAULIC
CHUCK

HCR

HYDRAULIC CHUCK (RADIAL TOOL LENGTH PRE-SETTING TYPE)

HYDRAULIK SPANNFUTTER (RADIALE WERKZEUGLÄGEN VOREINSTELLUNG)


MANDRIN HYDRAULIQUE (BANC DE PRÉ-RÉGLAGE RADIAL)

MANDRINI IDRAULICI (UTENSILI RADIALI PER AZZERAMENTO)

PORTAHERRAMIENTAS HIDRAULICO (AJUSTE DE LONGITUD TIPO PRE-SETTING)

HSK-A





DIN
69893-
HSK



2.5G







Unit : mm										
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L1	L2	WEIGHT (Kg)	
40A	HSK40A-HCR6-80	P2770210	6	26	34	80	36	27	0.55	
	HSK40A-HCR8-80	P2770211	8	28	34	80	36	27	0.55	
	HSK40A-HCR10-85	P2770212	10	30	34	85	43	32	0.65	
	HSK40A-HCR12-90	P2770213	12	32	34	90	48	37	0.70	
50A	HSK50A-HCR6-80	P2770214	6	26	40	80	35	27	0.70	
	HSK50A-HCR8-80	P2770215	8	28	40	80	36	27	0.70	
	HSK50A-HCR10-85	P2770216	10	30	40	85	38	32	0.73	
	HSK50A-HCR12-90	P2770217	12	32	40	90	40	37	0.80	
	HSK50A-HCR14-90	P2770218	14	34	40	90	40	42	0.80	
	HSK50A-HCR16-95	P2770219	16	38	53	95	36.5	42	1.00	
	HSK50A-HCR18-95	P2770220	18	40	57	95	36.5	42	1.00	
	HSK50A-HCR20-100	P2770221	20	42	60	100	39	42	1.10	
63A	HSK63A-HCR6-80	P2770205	6	26	50	80	33	27	0.96	
	HSK63A-HCR8-80	P2770206	8	28	50	80	33	27	0.98	
	HSK63A-HCR10-85	P2770207	10	30	50	85	38	32	1.04	
	HSK63A-HCR12-90	P2567011	12	32	50	90	40	37	1.06	
	HSK63A-HCR14-90	P2770202	14	34	50	90	46	37	1.08	
	HSK63A-HCR16-95	P2770209	16	38	50	95	51	42	1.18	
	HSK63A-HCR18-95	P2770203	18	40	50	95	52	42	1.20	
	HSK63A-HCR20-100	P2567012	20	42	50	100	51	42	1.22	
	HSK63A-HCR25-120	P2770204	25	57	63	120	54.5	48	2.20	
	HSK63A-HCR32-125	P2770201	32	64	75	125	57.5	55	2.60	
100A	HSK100A-HCR6-85	P2770222	6	26	63	85	33	27	3.60	
	HSK100A-HCR8-85	P2770223	8	28	63	85	33	27	3.60	
	HSK100A-HCR10-90	P2770224	10	30	63	90	36	32	3.80	
	HSK100A-HCR12-95	P2770225	12	32	63	95	40	37	3.80	
	HSK100A-HCR14-95	P2770226	14	34	63	95	41	37	3.80	
	HSK100A-HCR16-100	P2770227	16	38	63	100	46	42	3.90	
	HSK100A-HCR18-100	P2770228	18	40	63	100	46	42	3.90	
	HSK100A-HCR20-105	P2770229	20	42	75	105	51	42	4.20	
	HSK100A-HCR25-115	P2770230	25	57	75	115	55.5	48	4.40	
	HSK100A-HCR32-120	P2770231	32	64	75	120	63.5	55	4.60	

► Inch type products are available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

► Supplied with clamping T-wrench.

► For applicable Hydraulic Chuck collet, please refer to page D291~D294.



HYDRAULIC
CHUCK

HCP

HYDRAULIC CHUCK (Power E Hydro)


HYDRAULIK SPANNFUTTER (POWER E HYDRO)


MANDRIN HYDRAULIQUE (POWER E HYDRO)

MANDRINI IDRAULICI (POWER E HYDRO)

PORTAHERRAMIENTAS HIDRAULICO (POWER E HYDRO)

HSK-A





DIN
69893-
HSK



2.5G







Unit : mm												
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	D3	L	L1	L2	G	FIG.	WEIGHT (Kg)
63A	HSK63A-HC12P-80	P2770302P	12	32	42	52.5	80	34	41	M8x1.0	1	1.20
	HSK63A-HC20P-80	P2770301P	20	38	52.5	-	80	-	48	M8x1.0	2	1.30
100A	HSK100A-HC20P-90	P2770303P	20	38	52.5	-	90	-	48	M8x1.0	2	2.80
	HSK100A-HC32P-100	P2770304P	32	58.5	72	-	100	-	57	M8x1.0	2	3.70

► Inch type products are available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

► Supplied with clamping T-wrench.

► For applicable Hydraulic Chuck collet, please refer to page D291~D294.

D154

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS



HYDRAULIC
CHUCK

HCP

HYDRAULIC CHUCK (Power E Hydro)


HYDRAULIK SPANNFUTTER (POWER E HYDRO)


MANDRIN HYDRAULIQUE (POWER E HYDRO)

MANDRINI IDRAULICI (POWER E HYDRO)

PORTAHERRAMIENTAS HIDRAULICO (POWER E HYDRO)

HSK-A





DIN
69893-
HSK



2.5G







Unit : mm												
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	D3	L	L1	L2	G	FIG.	WEIGHT (Kg)
63A	HSK63A-HC12P-80	P2770302P	12	32	42	52.5	80	34	41	M8x1.0	1	1.20
	HSK63A-HC20P-80	P2770301P	20	38	52.5	-	80	-	48	M8x1.0	2	1.30
100A	HSK100A-HC20P-90	P2770303P	20	38	52.5	-	90	-	48	M8x1.0	2	2.80
	HSK100A-HC32P-100	P2770304P	32	58.5	72	-	100	-	57	M8x1.0	2	3.70

► Inch type products are available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

► Supplied with clamping T-wrench.

► For applicable Hydraulic Chuck collet, please refer to page D291~D294.

D155

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




HYDRAULIC
CHUCK


HC

HYDRAULIC CHUCK (STANDARD)

HYDRAULIK SPANNFUTTER (STANDARD)
MANDRIN HYDRAULIQUE (STANDARD)
MANDRINI IDRAULICI (STANDARD)
PORTAHERRAMIENTAS HIDRAULICO (ESTÁNDAR)

HSK-A





DIN
69893-
HSK

2.5G

25,000
RPM


(H: 3D)
≤ 3μm


AD

Unit : mm										
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L1	L2	G	WEIGHT (Kg)
32A	HSK32A-HC6-80	P2770413	6	26	40	80	29	27	M5×0.8	0.30
	HSK32A-HC8-80	P2770414	8	28	40	80	29	27	M6×1.0	0.30
	HSK32A-HC10-85	P2770415	10	30	40	85	35	32	M6×1.0	0.30
	HSK32A-HC12-90	P2770416	12	32	40	90	40	37	M6×1.0	0.30
40A	HSK40A-HC6-70	P2770401	6	26	34	70	36	27	M5×0.8	0.50
	HSK40A-HC8-70	P2770402	8	28	34	70	36	27	M6×1.0	0.50
	HSK40A-HC10-75	P2770403	10	30	34	75	42	32	M6×1.0	0.60
	HSK40A-HC12-80	P2770417	12	32	34	80	48	37	M6×1.0	0.65
50A	HSK50A-HC6-70	P2770404	6	26	40	70	28	27	M5×0.8	0.65
	HSK50A-HC8-70	P2770405	8	28	40	70	28	27	M6×1.0	0.65
	HSK50A-HC10-75	P2770406	10	30	40	75	34	32	M8×1.0	0.70
	HSK50A-HC12-85	P2770407	12	32	40	85	44	37	M10×1.0	0.75
	HSK50A-HC14-85	P2770408	14	34	40	85	43	37	M10×1.0	0.75
	HSK50A-HC16-90	P2770409	16	38	53	90	30	42	M12×1.0	0.90
	HSK50A-HC18-90	P2770418	18	40	57	90	30	42	M12×1.0	0.90
	HSK50A-HC20-90	P2770419	20	42	60	90	29	42	M16×1.0	1.00
63A	HSK63A-HC6-70	P2567001	6	26	50	70	24	27	M5×0.8	0.53
	HSK63A-HC8-70	P2567002	8	28	50	70	25	27	M6×1.0	0.55
	HSK63A-HC10-80	P2567003	10	30	50	80	35	32	M8×1.0	1.00
	HSK63A-HC12-85	P2567004	12	32	50	85	40	37	M10×1.0	1.03
	HSK63A-HC14-85	P2567005	14	34	50	85	40	37	M10×1.0	1.05
	HSK63A-HC16-90	P2567006	16	38	50	90	46	42	M12×1.0	1.15
	HSK63A-HC18-90	P2567007	18	40	50	90	47	42	M12×1.0	1.15
	HSK63A-HC20-90	P2567008	20	42	50	90	48	42	M16×1.0	1.20
	HSK63A-HC25-120	P2567009	25	57	63	120	59	48	M16×1.0	2.20
	HSK63A-HC32-125	P2567010	32	64	75	125	63	55	M16×1.0	2.40

► Inch type products are available.
► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.
► Supplied with clamping T-wrench.
► For applicable Hydraulic Chuck collet, please refer to page D291~D294.

► NEXT PAGE

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




HYDRAULIC
CHUCK


HC

HYDRAULIC CHUCK (STANDARD)

HYDRAULIK SPANNFUTTER (STANDARD)
MANDRIN HYDRAULIQUE (STANDARD)
MANDRINI IDRAULICI (STANDARD)
PORTAHERRAMIENTAS HIDRAULICO (ESTÁNDAR)

HSK-A





DIN
69893-
HSK

2.5G

25,000
RPM


(H: 3D)
≤ 3μm


AD

Unit : mm										
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L1	L2	G	WEIGHT (Kg)
80A	HSK80A-HC12-85	P2770462	12	32	50	85	40	37	M10×1.0	1.60
	HSK80A-HC20-95	P2770463	20	42	50	95	52	42	M16×1.0	1.80
	HSK80A-HC32-125	P2770464	32	64	75	125	63	55	M16×1.0	3.30
100A	HSK100A-HC6-75	P2770420	6	26	50	75	26	27	M5×0.8	3.20
	HSK100A-HC8-75	P2770421	8	28	50	75	26	27	M6×1.0	3.20
	HSK100A-HC10-90	P2770422	10	30	50	90	42	32	M8×1.0	3.40
	HSK100A-HC12-95	P2770410	12	32	50	95	47	37	M10×1.0	3.40
	HSK100A-HC14-95	P2770423	14	34	50	95	47	37	M10×1.0	3.40
	HSK100A-HC16-100	P2770411	16	38	50	100	53	42	M12×1.0	3.50
	HSK100A-HC18-100	P2770424	18	40	50	100	53	42	M12×1.0	3.60
	HSK100A-HC20-105	P2757010	20	42	50	105	59	42	M16×1.0	4.00
	HSK100A-HC25-110	P2770412	25	57	63	110	62	48	M16×1.0	4.20
	HSK100A-HC32-110	P2757020	32	64	75	110	62	55	M16×1.0	4.30

► Inch type products are available.
► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.
► Supplied with clamping T-wrench.
► For applicable Hydraulic Chuck collet, please refer to page D291~D294.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




HYDRAULIC
CHUCK

HC

HYDRAULIC CHUCK (STANDARD)

HYDRAULIK SPANNFUTTER (STANDARD)
MANDRIN HYDRAULIQUE (STANDARD)
MANDRINI IDRAULICI (STANDARD)
PORTAHERRAMIENTAS HIDRAULICO (ESTÁNDAR)

HSK-C



DIN
69893-
HSK

2.5G

25,000
RPM

⚡
(at 3D)
≤ 3μm

AD

Unit : mm										
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L1	L2	G	WEIGHT (Kg)
32C	HSK32C-HC6-65	P2770425	6	26	32	65	30	27	M5x0.8	0.30
	HSK32C-HC8-70	P2770426	8	28	32	70	34	27	M6x1.0	0.30
	HSK32C-HC10-75	P2770427	10	30	32	75	39	32	M6x1.0	0.30
	HSK32C-HC12-80	P2770428	12	32	32	80	-	37	M6x1.0	0.30
40C	HSK40C-HC6-60	P2770429	6	26	40	60	36	27	M5x0.8	0.55
	HSK40C-HC8-60	P2770430	8	28	40	60	36	27	M6x1.0	0.55
	HSK40C-HC10-65	P2770431	10	30	40	65	41	32	M6x1.0	0.65
	HSK40C-HC12-70	P2770432	12	32	40	70	47	37	M6x1.0	0.70
50C	HSK50C-HC6-60	P2770433	6	26	50	60	30	27	M5x0.8	0.65
	HSK50C-HC8-60	P2770434	8	28	50	60	30	27	M6x1.0	0.65
	HSK50C-HC10-65	P2770435	10	30	50	65	35	32	M8x1.0	0.70
	HSK50C-HC12-75	P2770436	12	32	50	75	44	37	M10x1.0	0.75
	HSK50C-HC14-75	P2770437	14	34	50	75	46	37	M10x1.0	0.75
	HSK50C-HC16-80	P2770438	16	38	50	80	51	42	M12x1.0	0.90
	HSK50C-HC18-80	P2770439	18	40	50	80	51	42	M12x1.0	0.90
63C	HSK50C-HC20-80	P2770440	20	42	50	80	48	42	M16x1.0	1.00
	HSK63C-HC6-60	P2770441	6	26	63	60	25	27	M5x0.8	0.96
	HSK63C-HC8-60	P2770442	8	28	63	60	25	27	M6x1.0	0.98
	HSK63C-HC10-65	P2770443	10	30	63	65	31	32	M8x1.0	1.04
	HSK63C-HC12-75	P2770444	12	32	63	75	41	37	M10x1.0	1.06
	HSK63C-HC14-75	P2770445	14	34	63	75	42	37	M10x1.0	1.08
	HSK63C-HC16-80	P2770446	16	38	63	80	48	42	M12x1.0	1.18
	HSK63C-HC18-80	P2770447	18	40	63	80	47	42	M12x1.0	1.20
	HSK63C-HC20-80	P2770448	20	42	63	80	49	42	M16x1.0	1.22
	HSK63C-HC25-95	P2770449	25	57	63	95	63	48	M16x1.0	2.20
	HSK63C-HC32-100	P2770450	32	63	63	100	-	55	M16x1.0	2.60

► Inch type products are available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

► Supplied with clamping T-wrench.

► For applicable Hydraulic Chuck collet, please refer to page D291~D294.

D158

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




HYDRAULIC
CHUCK

HC

HYDRAULIC CHUCK (STANDARD)

HYDRAULIK SPANNFUTTER (STANDARD)
MANDRIN HYDRAULIQUE (STANDARD)
MANDRINI IDRAULICI (STANDARD)
PORTAHERRAMIENTAS HIDRAULICO (ESTÁNDAR)

HSK-E



DIN
69893-
HSK

2.5G

25,000
RPM

⚡
(at 3D)
≤ 3μm

AD

Unit : mm										
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L1	L2	G	WEIGHT (Kg)
40E	HSK40E-HC6-70	P2770451	6	26	34	70	36	27	M5x0.8	0.55
	HSK40E-HC8-70	P2770452	8	28	34	70	36	27	M6x1.0	0.55
	HSK40E-HC10-75	P2770453	10	30	34	75	42	32	M6x1.0	0.65
	HSK40E-HC12-80	P2770454	12	32	34	80	48	37	M6x1.0	0.70
50E	HSK50E-HC6-70	P2770455	6	26	40	70	28	27	M5x0.8	0.65
	HSK50E-HC8-70	P2770456	8	28	40	70	28	27	M6x1.0	0.65
	HSK50E-HC10-75	P2770457	10	30	40	75	34	32	M8x1.0	0.70
	HSK50E-HC12-85	P2770458	12	32	40	85	44	37	M10x1.0	0.75
	HSK50E-HC16-90	P2770459	16	38	53	90	30	42	M12x1.0	0.90
63F	HSK50E-HC20-90	P2770460	20	42	60	90	29	42	M16x1.0	1.00
	HSK63F-HC20-85	P2770461	20	42	50	85	46	42	M12x1.0	1.20

► Inch type products are available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

► Supplied with clamping T-wrench.

► For applicable Hydraulic Chuck collet, please refer to page D291~D294.

D159

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




HYDRAULIC
CHUCK

HMC

HYDRAULIC CHUCK (SLIM)

HYDRAULIK SPANNFUTTER FÜR DEN FORMENBAU
MANDRIN HYDRAULIQUE POUR MOULISTE
MANDRINI IDRAULICI PER STAMPAGGIO
PORTAHERRAMIENTAS HIDRAULICO PARA MOLDES

HSK-A



DIN
69893-
HSK

2.5G

25,000
RPM

(at 3D)
≤ 3μm

AD

Unit : mm										
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L1	L2	G	WEIGHT (Kg)
63A	HSK63A-HMC6-145	P2770801	6	20	50	145	90	27	M5×0.8	1.40
	HSK63A-HMC8-145	P2770802	8	22	50	145	90	27	M6×1.0	1.40
	HSK63A-HMC10-145	P2770803	10	24	50	145	90	32	M8×1.0	1.40
	HSK63A-HMC12-145	P2770804	12	25	50	145	90	37	M10×1.0	1.40
	HSK63A-HMC14-145	P2770814	14	27	50	145	90	37	M10×1.0	1.40
	HSK63A-HMC16-145	P2770805	16	32	50	145	90	42	M12×1.0	1.45
	HSK63A-HMC20-145	P2770806	20	34	50	145	90	42	M16×1.0	1.50
100A	HSK100A-HMC6-150	P2770812	6	20	50	150	90	27	M5×0.8	4.50
	HSK100A-HMC8-150	P2770807	8	22	50	150	90	27	M6×1.0	4.50
	HSK100A-HMC10-150	P2770808	10	24	50	150	90	32	M8×1.0	4.50
	HSK100A-HMC12-150	P2770809	12	25	50	150	90	37	M10×1.0	4.50
	HSK100A-HMC14-150	P2770815	14	27	50	150	90	37	M10×1.0	4.50
	HSK100A-HMC16-150	P2770810	16	32	50	150	90	42	M12×1.0	4.70
	HSK100A-HMC20-150	P2770811	20	34	50	150	90	42	M16×1.0	5.00

► Inch type products are available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

► Supplied with clamping T-wrench.

► For applicable Hydraulic Chuck collet, please refer to page D291~D294.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




HYDRAULIC
CHUCK

HC-LS

HYDRAULIC CHUCK (LONG & SLIM)

HYDRAULIK SPANNFUTTER (LANG & SCHLANK)
MANDRIN HYDRAULIQUE (LONGUE ET MINCE)
MANDRINI IDRAULICI (LUNGO E SOTTILE)
PORTAHERRAMIENTAS HIDRAULICO (LARGO Y DELGADO)

HSK-A



DIN
69893-
HSK

2.5G

25,000
RPM

(at 3D)
≤ 3μm

AD

Unit : mm										
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L1	L2	G	WEIGHT (Kg)
63A	HSK63A-HC6LS-150	P2770483	6	26	50	150	103	25	M5×0.8	1.40
	HSK63A-HC6LS-200	P2770484	6	26	50	200	153	25	M5×0.8	1.60
	HSK63A-HC8LS-150	P2770485	8	28	50	150	104	25	M6×1.0	1.40
	HSK63A-HC8LS-200	P2770486	8	28	50	200	154	25	M6×1.0	1.60
	HSK63A-HC10LS-150	P2770487	10	30	50	150	104	29	M8×1.0	1.50
	HSK63A-HC10LS-200	P2770488	10	30	50	200	154	29	M8×1.0	1.70
	HSK63A-HC12LS-150	P2770489	12	32	50	150	105	34	M10×1.0	1.50
	HSK63A-HC12LS-200	P2770490	12	32	50	200	155	34	M10×1.0	1.80
	HSK63A-HC14LS-150	P2770491	14	34	50	150	105	34.5	M10×1.0	1.60
	HSK63A-HC16LS-150	P2770492	16	38	50	150	106	39	M12×1.0	1.80
	HSK63A-HC16LS-200	P2770493	16	38	50	200	156	39	M12×1.0	2.20
	HSK63A-HC18LS-150	P2770494	18	40	50	150	107	40.5	M12×1.0	1.80
	HSK63A-HC20LS-150	P2770495	20	42	50	150	108	40.5	M16×1.0	1.90
	HSK63A-HC20LS-200	P2770496	20	42	50	200	158	40.5	M16×1.0	2.40

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

► Supplied with clamping T-wrench.

► For applicable Hydraulic Chuck collet, please refer to page D291~D294.

D160

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

 YG-1 CO., LTD.


phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

D161



HSK-A

SCHRUMPFUTTER
MANDRIN DE FRETAGE
MADRINI PER CALLETAMENTO A CALDO
PORTAHERRAMIENTAS DE COMPRESION POR CALOR



										Unit : mm
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L2	G	FIG.	WEIGHT (Kg)
100A	HSK100A-SFH14-95	P2771476	14	27	34	95	47	M10×1.0	1	1.40
	HSK100A-SFH14-130	P2860059	14	27	34	130	47	M10×1.0	1	-
	HSK100A-SFH14-160	P2771477	14	27	34	160	47	M10×1.0	1	1.90
	HSK100A-SFH14-200	P2860060	14	27	34	200	47	M10×1.0	1	-
	HSK100A-SFH16-100	P2771478	16	27	34	100	50	M12×1.0	1	1.40
	HSK100A-SFH16-130	P2860061	16	27	34	130	50	M12×1.0	1	-
	HSK100A-SFH16-160	P2771479	16	27	34	160	50	M12×1.0	1	1.90
	HSK100A-SFH16-200	P2860062	16	27	34	200	50	M12×1.0	1	-
	HSK100A-SFH18-100	P2771480	18	33	42	100	50	M12×1.0	2	1.50
	HSK100A-SFH18-130	P2860063	18	33	42	130	50	M12×1.0	2	-
	HSK100A-SFH18-160	P2771481	18	33	42	160	50	M12×1.0	2	2.00
	HSK100A-SFH18-200	P2860064	18	33	42	200	50	M12×1.0	2	-
	HSK100A-SFH20-100	P2771482	20	33	42	100	52	M16×1.0	2	1.50
	HSK100A-SFH20-130	P2860065	20	33	42	130	52	M16×1.0	2	-
	HSK100A-SFH20-160	P2771483	20	33	42	160	52	M16×1.0	2	2.00
	HSK100A-SFH20-200	P2860066	20	33	42	200	52	M16×1.0	2	-
	HSK100A-SFH25-115	P2771484	25	44	53	115	58	M16×1.0	2	1.80
	HSK100A-SFH25-130	P2860067	25	44	53	130	58	M16×1.0	2	-
HSK100A-SFH25-160	P2771485	25	44	53	160	58	M16×1.0	2	2.30	
HSK100A-SFH25-200	P2860068	25	44	53	200	58	M16×1.0	2	-	

- ▶ Inch type products are available.
- ▶ Supplied without balancing screws.
- ▶ Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

TOOLING SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS



SHRINK FIT
HOLDER


SFH

SHRINK FIT HOLDER (COOLANT CHANNEL)

SCHRUMPFUTTER
MANDRIN DE FRETAGE
MADRINI PER CALLETAMENTO A CALDO
PORTAHERRAMIENTAS DE COMPRESION POR CALOR

HSK-A





DIN
69893-
HSK

2.5G


25,000
RPM

LDI
≤ 3µm

AD+C

Unit : mm									
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L2	G	WEIGHT (Kg)
63A	HSK63A-SFH3C-80*1	P2862131C	3	12	17	80	10	-	-
	HSK63A-SFH4C-80*1	P2862132C	4	12	17	80	12	-	-
	HSK63A-SFH5C-80*1	P2862133C	5	12	17	80	15	-	-
	HSK63A-SFH6C-80	P2862013C	6	21	27	80	36	M5x0.8	0.83
	HSK63A-SFH6C-130	P2863400C	6	21	27	130	36	M5x0.8	-
	HSK63A-SFH6C-160	P2862014C	6	21	27	160	36	M5x0.8	1.00
	HSK63A-SFH8C-80	P2862015C	8	21	27	80	36	M6x1.0	0.83
	HSK63A-SFH8C-130	P2863401C	8	21	27	130	36	M6x1.0	-
	HSK63A-SFH8C-160	P2862016C	8	21	27	160	36	M6x1.0	1.00
	HSK63A-SFH10C-85	P2862017C	10	24	32	85	42	M8x1.0	0.83
	HSK63A-SFH10C-130	P2863402C	10	24	32	130	42	M8x1.0	-
	HSK63A-SFH10C-160	P2862018C	10	24	32	160	42	M8x1.0	1.00
	HSK63A-SFH12C-90	P2862019C	12	24	32	90	47	M10x1.0	0.83
	HSK63A-SFH12C-130	P2863403C	12	24	32	130	47	M10x1.0	-
	HSK63A-SFH12C-160	P2862020C	12	24	32	160	47	M10x1.0	1.00
	HSK63A-SFH14C-90	P2862021C	14	27	34	90	47	M10x1.0	0.91
	HSK63A-SFH14C-130	P2863404C	14	27	34	130	47	M10x1.0	-
	HSK63A-SFH14C-160	P2862022C	14	27	34	160	47	M10x1.0	1.30
	HSK63A-SFH16C-95	P2862023C	16	27	34	95	50	M12x1.0	0.98
	HSK63A-SFH16C-130	P2863405C	16	27	34	130	50	M12x1.0	-
	HSK63A-SFH16C-160	P2862024C	16	27	34	160	50	M12x1.0	1.40
	HSK63A-SFH18C-95	P2862025C	18	33	42	95	50	M12x1.0	0.98
	HSK63A-SFH18C-130	P2863406C	18	33	42	130	50	M12x1.0	-
	HSK63A-SFH18C-160	P2862026C	18	33	42	160	50	M12x1.0	1.40
	HSK63A-SFH20C-100	P2862027C	20	33	42	100	52	M16x1.0	1.00
	HSK63A-SFH20C-130	P2863407C	20	33	42	130	52	M16x1.0	-
	HSK63A-SFH20C-160	P2862028C	20	33	42	160	52	M16x1.0	1.40
	HSK63A-SFH25C-115	P2862029C	25	44	53	115	58	M16x1.0	1.40
	HSK63A-SFH25C-130	P2862142C	25	44	53	130	58	M16x1.0	-
	HSK63A-SFH25C-160	P2862030C	25	44	53	160	58	M16x1.0	1.80

► Inch type products are available.
► Supplied without balancing screws.
► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.
► With two coolant channel bores.
► Resealable coolant channel type is available upon request.
(Thread for plugging screw & 2 screws)
► *1 Resealable type is not available.



► NEXT PAGE

D168

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS



SHRINK FIT
HOLDER


SFH

SHRINK FIT HOLDER (COOLANT CHANNEL)

SCHRUMPFUTTER
MANDRIN DE FRETAGE
MADRINI PER CALLETAMENTO A CALDO
PORTAHERRAMIENTAS DE COMPRESION POR CALOR

HSK-A





DIN
69893-
HSK

2.5G


25,000
RPM

LDI
≤ 3µm

AD+C

Unit : mm									
TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L2	G	WEIGHT (Kg)
100A	HSK100A-SFH3C-85*1	P2862143C	3	12	17	85	10	-	-
	HSK100A-SFH4C-85*1	P2862144C	4	12	17	85	12	-	-
	HSK100A-SFH5C-85*1	P2862145C	5	12	17	85	15	-	-
	HSK100A-SFH6C-85	P2862031C	6	21	27	85	36	M5x0.8	1.30
	HSK100A-SFH6C-130	P2863408C	6	21	27	130	36	M5x0.8	-
	HSK100A-SFH6C-160	P2862032C	6	21	27	160	36	M5x0.8	1.80
	HSK100A-SFH6C-200	P2863409C	6	21	27	200	36	M5x0.8	-
	HSK100A-SFH8C-85	P2862033C	8	21	27	85	36	M6x1.0	1.30
	HSK100A-SFH8C-130	P2863410C	8	21	27	130	36	M6x1.0	-
	HSK100A-SFH8C-160	P2862034C	8	21	27	160	36	M6x1.0	1.80
	HSK100A-SFH8C-200	P2863411C	8	21	27	200	36	M6x1.0	-
	HSK100A-SFH10C-90	P2862035C	10	24	32	90	42	M8x1.0	1.30
	HSK100A-SFH10C-130	P2863412C	10	24	32	130	42	M8x1.0	-
	HSK100A-SFH10C-160	P2862036C	10	24	32	160	42	M8x1.0	1.80
	HSK100A-SFH10C-200	P2863413C	10	24	32	200	42	M8x1.0	-
	HSK100A-SFH12C-95	P2862037C	12	24	32	95	47	M10x1.0	1.30
	HSK100A-SFH12C-130	P2863414C	12	24	32	130	47	M10x1.0	-
	HSK100A-SFH12C-160	P2862038C	12	24	32	160	47	M10x1.0	1.80
	HSK100A-SFH12C-200	P2863415C	12	24	32	200	47	M10x1.0	-
	HSK100A-SFH14C-95	P2862039C	14	27	34	95	47	M10x1.0	1.40
	HSK100A-SFH14C-130	P2863416C	14	27	34	130	47	M10x1.0	-
	HSK100A-SFH14C-160	P2862040C	14	27	34	160	47	M10x1.0	1.90
	HSK100A-SFH14C-200	P2863417C	14	27	34	200	47	M10x1.0	-
	HSK100A-SFH16C-100	P2862041C	16	27	34	100	50	M12x1.0	1.40
	HSK100A-SFH16C-130	P2863418C	16	27	34	130	50	M12x1.0	-
	HSK100A-SFH16C-160	P2862042C	16	27	34	160	50	M12x1.0	1.90
	HSK100A-SFH16C-200	P2863419C	16	27	34	200	50	M12x1.0	-

► Inch type products are available.
► Supplied without balancing screws.
► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.
► With two coolant channel bores.
► Resealable coolant channel type is available upon request.
(Thread for plugging screw & 2 screws)
► *1 Resealable type is not available.



► NEXT PAGE

D169

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING SYSTEM

SK (DIN 69871)

CBT (BT DUAL CONTACT)

BT (JIS B6339/ MAS 403)

HSK (DIN 69893/ ISO 12164)

STRAIGHT

ISO, NT, MTA/MTB, GOST

TOOL HOLDER SET

BORING SYSTEM

ACCESSORY & PARTS

SHRINK FIT HOLDER

SFH

SHRINK FIT HOLDER

SCHRUMPFUTTER
MANDRIN DE FRETAGE
MADRINI PER CALLETAMENTO A CALDO
PORTAHERRAMIENTAS DE COMPRESION POR CALOR

HSK-E



FIG.1

FIG.2

DIN 69893-HSK

2.5G

25,000 RPM

LD ≤ 3μm

AD

TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L2	G	FIG.	WEIGHT (Kg)
25E	HSK25E-SFH3-45	P2771420	3	11	15	45	10	-	1	-
	HSK25E-SFH4-45	P2771421	4	11	15	45	12	-	1	-
	HSK25E-SFH5-45	P2771422	5	11	15	45	15	-	1	-
	HSK25E-SFH6-45	P2771423	6	12	17	45	18	-	2	-
	HSK25E-SFH8-45	P2771424	8	14	18	45	30	-	2	-
	HSK25E-SFH10-50	P2771425	10	16	20	50	37	-	2	-
32E	HSK32E-SFH3-60	P2771426	3	11	15	60	10	-	1	0.40
	HSK32E-SFH4-60	P2771427	4	11	15	60	12	-	1	0.50
	HSK32E-SFH5-60	P2771428	5	11	15	60	15	-	1	0.40
	HSK32E-SFH6-70	P2771429	6	12	17	70	18	-	2	0.50
	HSK32E-SFH8-70	P2771430	8	14	18	70	30	-	2	0.50
	HSK32E-SFH10-80	P2771431	10	16	20	80	37	-	2	0.60
40E	HSK40E-SFH3-60	P2771432	3	11	15	60	10	-	1	0.30
	HSK40E-SFH3-80	P2771433	3	11	15	80	10	-	1	0.40
	HSK40E-SFH4-60	P2771434	4	11	15	60	12	-	1	0.30
	HSK40E-SFH4-80	P2771435	4	11	15	80	12	-	1	0.40
	HSK40E-SFH5-60	P2771436	5	11	15	60	15	-	1	0.30
	HSK40E-SFH5-80	P2771437	5	11	15	80	15	-	1	0.40
	HSK40E-SFH6-60	P2771438	6	21	27	60	36	M5×0.8	2	0.40
	HSK40E-SFH6-80	P2771439	6	21	27	80	36	M5×0.8	2	0.50
	HSK40E-SFH8-70	P2771440	8	21	27	70	36	M6×1.0	2	0.40
	HSK40E-SFH8-90	P2771441	8	21	27	90	36	M6×1.0	2	0.50
	HSK40E-SFH10-70	P2771442	10	24	32	70	42	M8×1.0	2	0.50
	HSK40E-SFH10-90	P2771443	10	24	32	90	42	M8×1.0	2	0.60

Unit : mm

► Inch type products are available.
► Supplied without balancing screws.
► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

TOOLING SYSTEM

SK (DIN 69871)

CBT (BT DUAL CONTACT)

BT (JIS B6339/ MAS 403)

HSK (DIN 69893/ ISO 12164)

STRAIGHT

ISO, NT, MTA/MTB, GOST

TOOL HOLDER SET

BORING SYSTEM

ACCESSORY & PARTS


SHRINK FIT HOLDER

SFH

SHRINK FIT HOLDER (CURVED)

SCHRUMPFUTTER (GEBOGEN)
MANDRIN DE FRETAGE (INCURVÉ)
MADRINI PER CALLETAMENTO A CALDO (CURVO)
PORTAHERRAMIENTAS DE COMPRESION POR CALOR (CURVADO)

HSK-A



DIN 69893-HSK

2.5G

25,000 RPM

LD ≤ 3μm

AD

TAPER No.	MODEL No.	EDP No.	d1	D1	D2	L	L1	WEIGHT (Kg)
63A	HSK63A-SFH4CV-120	P2785100CV	4	10	53	120	12	-
	HSK63A-SFH4CV-150	P2785101CV	4	10	53	150	12	-
	HSK63A-SFH6CV-90	P2785102CV	6	13	53	90	18	-
	HSK63A-SFH6CV-120	P2785103CV	6	13	53	120	18	-
	HSK63A-SFH6CV-150	P2785104CV	6	13	53	150	18	-
	HSK63A-SFH8CV-90	P2785105CV	8	16	53	90	24	-
	HSK63A-SFH8CV-120	P2785106CV	8	16	53	120	24	-
	HSK63A-SFH8CV-150	P2785107CV	8	16	53	150	24	-
	HSK63A-SFH10CV-90	P2785108CV	10	19	53	90	30	-
	HSK63A-SFH10CV-120	P2785109CV	10	19	53	120	30	-
	HSK63A-SFH10CV-150	P2785110CV	10	19	53	150	30	-
	HSK63A-SFH12CV-90	P2785111CV	12	22	53	90	30	-
	HSK63A-SFH12CV-120	P2785112CV	12	22	53	120	30	-
	HSK63A-SFH12CV-150	P2785113CV	12	22	53	150	30	-
100A	HSK100A-SFH8CV-195	P2785114CV	8	16	85	195	24	-
	HSK100A-SFH8CV-225	P2785115CV	8	16	85	225	24	-
	HSK100A-SFH10CV-165	P2785116CV	10	19	85	165	30	-
	HSK100A-SFH10CV-195	P2785117CV	10	19	85	195	30	-
	HSK100A-SFH10CV-225	P2785118CV	10	19	85	225	30	-
	HSK100A-SFH12CV-165	P2785119CV	12	22	85	165	30	-
	HSK100A-SFH12CV-195	P2785120CV	12	22	85	195	30	-
	HSK100A-SFH12CV-225	P2785121CV	12	22	85	225	30	-

► Inch type products are available.
► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

D172

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

D173

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS



ER COLLET
CHUCK


ER

ER COLLET CHUCK

SPANN FUTTER - ER
MANDRIN À PINCES - ER
MANDRINO PORTA PINZE - ER
PORTAPINZAS - ER

HSK-A





DIN
69893-
HSK

2.5G

25,000
RPM

AD

Unit : mm									
TAPER No.	MODEL No.	EDP No.	CLAMPING RANGE	L	D	G	H	NUT / COLLET	WEIGHT (Kg)
50A	HSK50A-ER16-100	P2774938	0.5 - 10.0	100	28	M10	45	ER16	0.70
	HSK50A-ER20-100	P2774939	0.5 - 13.0	100	35	M12	50	ER20	0.90
	HSK50A-ER25-100	P2774940	1.0 - 16.0	100	42	M12	50	ER25	1.20
	HSK50A-ER32-100	P2774941	1.0 - 20.0	100	50	M12	47	ER32	1.50
63A	HSK63A-ER16-100	P2774901	0.5 - 10.0	100	28	M10	45	ER16	1.20
	HSK63A-ER16-130	P2774966	0.5 - 10.0	130	28	M10	45	ER16	-
	HSK63A-ER16-160	P2771977	0.5 - 10.0	160	28	M10	45	ER16	-
	HSK63A-ER20-100	P2774942	0.5 - 13.0	100	35	M12	50	ER20	1.50
	HSK63A-ER20-130	P2774967	0.5 - 13.0	130	35	M12	50	ER20	-
	HSK63A-ER20-160	P2774968	0.5 - 13.0	160	35	M12	50	ER20	-
	HSK63A-ER25-100	P2774902	1.0 - 16.0	100	42	M12	57	ER25	1.80
	HSK63A-ER25-130	P2774969	1.0 - 16.0	130	42	M12	57	ER25	-
	HSK63A-ER25-160	P2774970	1.0 - 16.0	160	42	M12	57	ER25	-
	HSK63A-ER32-100	P2774903	1.0 - 20.0	100	50	M12	60	ER32	2.00
	HSK63A-ER32-130	P2774971	1.0 - 20.0	130	50	M12	60	ER32	-
	HSK63A-ER32-160	P2774954	1.0 - 20.0	160	50	M12	60	ER32	-
	HSK63A-ER40-120	P2774904	2.0 - 30.0	120	63	M12	69	ER40	2.30
	HSK63A-ER40-160	P2774972	2.0 - 30.0	160	63	M12	69	ER40	-

► Inch type products are available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

► For applicable ER collet, please refer to page D296~D304.

► For applicable ER nut, Sealing disk and Spanner, please refer to page D305~D309.

► NEXT PAGE

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS



ER COLLET
CHUCK


ER

ER COLLET CHUCK

SPANN FUTTER - ER
MANDRIN À PINCES - ER
MANDRINO PORTA PINZE - ER
PORTAPINZAS - ER

HSK-A





DIN
69893-
HSK

2.5G

25,000
RPM

AD

Unit : mm									
TAPER No.	MODEL No.	EDP No.	CLAMPING RANGE	L	D	G	H	NUT / COLLET	WEIGHT (Kg)
80A	HSK80A-ER16-100	P2774943	0.5 - 10.0	100	28	M10	45	ER16	1.77
	HSK80A-ER25-100	P2774944	1.0 - 16.0	100	42	M12	47	ER20	1.79
	HSK80A-ER32-100	P2774945	1.0 - 20.0	100	50	M12	53	ER25	1.95
100A	HSK100A-ER16-100	P2774905	0.5 - 10.0	100	28	M10	45	ER16	2.60
	HSK100A-ER16-130	P2774973	0.5 - 10.0	130	28	M10	45	ER16	-
	HSK100A-ER16-160	P2782001	0.5 - 10.0	160	28	M10	45	ER16	-
	HSK100A-ER20-100	P2774946	0.5 - 13.0	100	35	M12	50	ER20	2.70
	HSK100A-ER20-130	P2774974	0.5 - 13.0	130	35	M12	50	ER20	-
	HSK100A-ER20-160	P2782002	0.5 - 13.0	160	35	M12	50	ER20	-
	HSK100A-ER25-100	P2774906	1.0 - 16.0	100	42	M12	57	ER25	2.90
	HSK100A-ER25-130	P2774975	1.0 - 16.0	130	42	M12	57	ER25	-
	HSK100A-ER25-160	P2782003	1.0 - 16.0	160	42	M12	57	ER25	-
	HSK100A-ER32-100	P2774907	1.0 - 20.0	100	50	M12	65	ER32	3.10
	HSK100A-ER32-130	P2774976	1.0 - 20.0	130	50	M12	65	ER32	-
	HSK100A-ER32-160	P2774977	1.0 - 20.0	160	50	M12	65	ER32	-
	HSK100A-ER40-120	P2774947	1.0 - 20.0	120	63	M12	69	ER40	3.30
	HSK100A-ER40-160	P2774978	1.0 - 20.0	160	63	M12	69	ER40	-

► Inch type products are available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

► For applicable ER collet, please refer to page D296~D304.

► For applicable ER nut, Sealing disk and Spanner, please refer to page D305~D309.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS

ER COLLET
CHUCK

ER

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS

ER COLLET
CHUCK

ER

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS

ER COLLET CHUCK (SLIM)

SPANN FUTTER - ER
MANDRIN À PINCES - ER
MANDRINO PORTA PINZE - ER
PORTAPINZAS - ER

HSK-E

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS

DIN
69893-
HSK

2.5G

25,000
RPM

AD

Unit : mm								
TAPER No.	MODEL No.	EDP No.	CLAMPING RANGE	L	D	H	NUT / COLLET	WEIGHT (Kg)
25E	HSK25E-ER8M-35	P2774928	0.5 - 5.0	35	12	21.0	ER8M / ER8	0.15
	HSK25E-ER11M-40	P2774929	0.5 - 7.0	40	16	24.5	ER11M / ER11	0.18
32E	HSK32E-ER8M-40	P2774930	0.5 - 5.0	40	12	21.0	ER8M / ER8	0.15
	HSK32E-ER11M-40	P2774931	0.5 - 7.0	40	16	23.0	ER11M / ER11	0.18
	HSK32E-ER16M-60	P2774932	0.5 - 10.0	60	22	38.0	ER16M / ER16	0.21
40E	HSK32E-ER20M-60	P2774933	0.5 - 13.0	60	28	39.5	ER20M / ER20	0.21
	HSK40E-ER11M-75	P2774934	0.5 - 7.0	75	16	29.5	ER11M / ER11	0.40
	HSK40E-ER16M-80	P2774935	0.5 - 10.0	80	22	38.0	ER16M / ER16	0.50
	HSK40E-ER20M-80	P2774936	0.5 - 13.0	80	28	44.5	ER20M / ER20	0.70
	HSK40E-ER25M-80	P2774937	1.0 - 16.0	80	35	52.0	ER25M / ER25	0.80

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

DIN
69893-
HSK

6.3G

15,000
RPM

AD

Unit : mm								
TAPER No.	MODEL No.	EDP No.	CLAMPING RANGE	L	D	H	NUT / COLLET	WEIGHT (Kg)
25E	HSK25E-ER8M-35	P2771937	0.5 - 5.0	35	12	21.0	ER8M / ER8	0.10
	HSK25E-ER11M-40	P2771938	0.5 - 7.0	40	16	24.5	ER11M / ER11	0.10
32E	HSK32E-ER8M-40	P2774948	0.5 - 5.0	40	12	21.0	ER8M / ER8	0.15
	HSK32E-ER11M-40	P2774949	0.5 - 7.0	40	16	23.0	ER11M / ER11	0.15
	HSK32E-ER16M-60	P2774950	0.5 - 10.0	60	22	38.0	ER16M / ER16	0.21
	HSK32E-ER20M-60	P2774951	0.5 - 13.0	60	28	39.5	ER20M / ER20	0.20
40E	HSK40E-ER11M-75	P2771904	0.5 - 7.0	75	16	29.5	ER11M / ER11	0.40
	HSK40E-ER16M-80	P2771905	0.5 - 10.0	80	22	38.0	ER16M / ER16	0.50
	HSK40E-ER20M-80	P2771906	0.5 - 13.0	80	28	44.5	ER20M / ER20	0.70
	HSK40E-ER25M-80	P2771907	1.0 - 16.0	80	35	52.0	ER25M / ER25	0.80

► Inch type products are available.
► For applicable ER collet, please refer to page D296~D304.
► For applicable ER nut, Sealing disk and Spanner, please refer to page D307 & D309.

YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

ER COLLET CHUCK (SLIM)

SPANN FUTTER - ER
MANDRIN À PINCES - ER
MANDRINO PORTA PINZE - ER
PORTAPINZAS - ER

HSK-A

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS

DIN
69893-
HSK

6.3G

15,000
RPM

AD

Unit : mm									
TAPER No.	MODEL No.	EDP No.	CLAMPING RANGE	L	D	G	H	NUT / COLLET	WEIGHT (Kg)
50A	HSK50A-ER11M-75	P2802501	0.5 - 7.0	75	16	M6	29.5	ER11M / ER11	0.30
	HSK50A-ER16M-85	P2802502	0.5 - 10.0	85	22	M10	38.0	ER16M / ER16	0.40
	HSK50A-ER20M-90	P2802503	0.5 - 13.0	90	28	M12	44.5	ER20M / ER20	0.80
	HSK50A-ER25M-105	P2802504	1.0 - 16.0	105	35	M12	52.0	ER25M / ER25	1.20
63A	HSK63A-ER11M-75	P2802505	0.5 - 7.0	75	16	M6	29.5	ER11M / ER11	0.80
	HSK63A-ER11M-100	P2774963	0.5 - 7.0	100	16	M6	29.5	ER11M / ER11	-
	HSK63A-ER11M-130	P2802767	0.5 - 7.0	130	16	M6	29.5	ER11M / ER11	-
	HSK63A-ER11M-160	P2802768	0.5 - 7.0	160	16	M6	29.5	ER11M / ER11	-
	HSK63A-ER16M-85	P2802506	0.5 - 10.0	85	22	M10	38.0	ER16M / ER16	1.00
	HSK63A-ER16M-100	P2802769	0.5 - 10.0	100	22	M10	38.0	ER16M / ER16	-
	HSK63A-ER16M-130	P2802770	0.5 - 10.0	130	22	M10	38.0	ER16M / ER16	-
	HSK63A-ER16M-160	P2802771	0.5 - 10.0	160	22	M10	38.0	ER16M / ER16	-
	HSK63A-ER20M-95	P2802507	0.5 - 13.0	95	28	M12	44.5	ER20M / ER20	1.20
	HSK63A-ER20M-130	P2802772	0.5 - 13.0	130	28	M12	44.5	ER20M / ER20	-
	HSK63A-ER20M-160	P2802773	0.5 - 13.0	160	28	M12	44.5	ER20M / ER20	-
	HSK63A-ER25M-105	P2802508	1.0 - 16.0	105	35	M12	52.0	ER25M / ER25	1.40
	HSK63A-ER25M-130	P2802774	1.0 - 16.0	130	35	M12	52.0	ER25M / ER25	-
	HSK63A-ER25M-160	P2802775	1.0 - 16.0	160	35	M12	52.0	ER25M / ER25	-
100A	HSK100A-ER11M-85	P2802509	0.5 - 7.0	85	16	M6	29.5	ER11M / ER11	2.40
	HSK100A-ER16M-95	P2802510	0.5 - 10.0	95	22	M10	38.0	ER16M / ER16	2.70
	HSK100A-ER20M-100	P2802511	0.5 - 13.0	100	28	M12	44.5	ER20M / ER20	3.00
	HSK100A-ER25M-120	P2802512	1.0 - 16.0	120	35	M12	52.0	ER25M / ER25	3.20

► Inch type products are available.
► For applicable ER collet, please refer to page D296~D304.
► For applicable ER nut, Sealing disk and Spanner, please refer to page D307 & D309.

D184

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

D185

TOOLING SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL HOLDER SET

BORING SYSTEM

ACCESSORY & PARTS

END MILL HOLDER

FRÄSERFUTTER UND FLÄCHENSPANNFUTTER

MANDRIN PORTE FRAISE À QUEUE CYLINDRIQUE, À MÉPLAT

MANDRINI PORTA FRESA TIPO WELDON

PORTAFRESAS Y EJES DE SUJECCION LATERAL


EMH

HSK-A



FIG.1

FIG.2



DIN 69893-HSK

2.5G

25,000 RPM

AD

Unit : mm											
TAPER No.	MODEL No.	EDP No.	d1	D2	L	L1	L2	L3	M	FIG.	WEIGHT (Kg)
40A	HSK40A-EMH6-60	P2775522	6	25	60	38	18	-	M6	1	0.30
	HSK40A-EMH8-60	P2775523	8	28	60	38	18	-	M8	1	0.30
	HSK40A-EMH10-60	P2775524	10	35	60	42	20	-	M10	1	0.30
	HSK40A-EMH12-70	P2775525	12	42	70	47	22.5	-	M12	1	0.40
	HSK40A-EMH14-70	P2775526	14	44	70	47	22.5	-	M12	1	0.40
	HSK40A-EMH16-80	P2775527	16	48	80	50	24	-	M14	1	0.60
50A	HSK50A-EMH6-65	P2775528	6	25	65	38	18	-	M6	1	0.70
	HSK50A-EMH8-65	P2775529	8	28	65	38	18	-	M8	1	0.80
	HSK50A-EMH10-65	P2775530	10	35	65	42	20	-	M10	1	0.80
	HSK50A-EMH12-80	P2775531	12	42	80	47	22.5	-	M12	1	1.20
	HSK50A-EMH14-80	P2775532	14	44	80	47	22.5	-	M12	1	1.30
	HSK50A-EMH16-80	P2775533	16	48	80	50	24	-	M14	1	1.30
	HSK50A-EMH18-80	P2775534	18	50	80	50	24	-	M14	1	1.40
	HSK50A-EMH20-80	P2775535	20	52	80	52	25	-	M16	1	1.50
63A	HSK63A-EMH6-65	P2775501	6	25	65	35	18	-	M6	1	0.80
	HSK63A-EMH8-65	P2775502	8	28	65	38	18	-	M8	1	0.80
	HSK63A-EMH10-65	P2775503	10	35	65	42	20	-	M10	1	0.90
	HSK63A-EMH12-80	P2775504	12	42	80	47	22.5	-	M12	1	1.10
	HSK63A-EMH14-80	P2775505	14	44	80	47	22.5	-	M12	1	1.20
	HSK63A-EMH16-80	P2775506	16	48	80	50	24	-	M14	1	1.30
	HSK63A-EMH18-80	P2775507	18	50	80	50	24	-	M14	1	1.40
	HSK63A-EMH20-80	P2775508	20	52	80	52	25	-	M16	1	1.50
	HSK63A-EMH25-110	P2775509	25	65	110	60	24	25	M18	2	2.30
	HSK63A-EMH32-110	P2775510	32	72	110	64	24	28	M20	2	2.60
100A	HSK100A-EMH6-80	P2775511	6	25	80	35	18	-	M6	1	0.80
	HSK100A-EMH8-80	P2775512	8	28	80	35	18	-	M8	1	0.80
	HSK100A-EMH10-80	P2775513	10	35	80	39	20	-	M10	1	0.90
	HSK100A-EMH12-80	P2775514	12	42	80	47	22.5	-	M12	1	1.10
	HSK100A-EMH14-80	P2775515	14	44	80	47	22.5	-	M12	1	1.20
	HSK100A-EMH16-100	P2775516	16	48	100	50	24	-	M14	1	1.30
	HSK100A-EMH18-100	P2775517	18	50	100	50	24	-	M14	1	1.40
	HSK100A-EMH20-100	P2775518	20	52	100	52	25	-	M16	1	1.50
	HSK100A-EMH25-100	P2775519	25	65	100	60	24	25	M18	2	2.30
	HSK100A-EMH32-100	P2775520	32	72	100	64	24	28	M20	2	2.60
	HSK100A-EMH40-120	P2775521	40	80	120	74	30	32	M20	2	2.60

► Inch type products are available.

► Standard End Mill Holder is for a cutting tool with weldon shank and End Mill Holder for a cutting tool with Whistle notch is available upon request.

► Combi-style Holder with ball jointed clamping screw which can be used with cutting tools with Weldon and Whistle notch shank is available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

D186

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

TOOLING SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL HOLDER SET

BORING SYSTEM

ACCESSORY & PARTS

END MILL HOLDER (COOLANT CHANNEL)

FRÄSERFUTTER UND FLÄCHENSPANNFUTTER

MANDRIN PORTE FRAISE À QUEUE CYLINDRIQUE, À MÉPLAT

MANDRINI PORTA FRESA TIPO WELDON

PORTAFRESAS Y EJES DE SUJECCION LATERAL


EMH

HSK-A



FIG.1

FIG.2



DIN 69893-HSK

2.5G

25,000 RPM

AD+C

Unit : mm											
TAPER No.	MODEL No.	EDP No.	d1	D2	L	L1	L2	L3	M	FIG.	WEIGHT (Kg)
40A	HSK40A-EMH6C-60	P2563061	6	25	60	38	18	-	M6	1	0.30
	HSK40A-EMH8C-60	P2563062	8	28	60	38	18	-	M8	1	0.30
	HSK40A-EMH10C-60	P2563063	10	35	60	42	20	-	M10	1	0.30
	HSK40A-EMH12C-70	P2563064	12	42	70	47	22.5	-	M12	1	0.40
	HSK40A-EMH14C-70	P2563065	14	44	70	47	22.5	-	M12	1	0.40
	HSK40A-EMH16C-80	P2563066	16	48	80	50	24	-	M14	1	0.60
50A	HSK50A-EMH6C-65	P2563067	6	25	65	38	18	-	M6	1	0.70
	HSK50A-EMH8C-65	P2563068	8	28	65	38	18	-	M8	1	0.80
	HSK50A-EMH10C-65	P2563069	10	35	65	42	20	-	M10	1	0.80
	HSK50A-EMH12C-80	P2563070	12	42	80	47	22.5	-	M12	1	1.20
	HSK50A-EMH14C-80	P2563071	14	44	80	47	22.5	-	M12	1	1.30
	HSK50A-EMH16C-80	P2563072	16	48	80	50	24	-	M14	1	1.30
	HSK50A-EMH18C-80	P2563073	18	50	80	50	24	-	M14	1	1.40
	HSK50A-EMH20C-80	P2563074	20	52	80	52	25	-	M16	1	1.50
	HSK63A-EMH6C-65	P2563021	6	25	65	35	18	-	M6	1	0.80
	HSK63A-EMH8C-65	P2563022	8	28	65	40	18	-	M8	1	0.80
63A	HSK63A-EMH10C-65	P2563023	10	35	65	40.5	20	-	M10	1	0.90
	HSK63A-EMH12C-80	P2563024	12	42	80	49	22.5	-	M12	1	1.10
	HSK63A-EMH14C-80	P2563025	14	44	80	49	22.5	-	M12	1	1.20
	HSK63A-EMH16C-80	P2563026	16	48	80	52	24	-	M14	1	1.30
	HSK63A-EMH18C-80	P2563027	18	50	80	52	24	-	M14	1	1.40
	HSK63A-EMH20C-80	P2563028	20	52	80	53	25	-	M16	1	1.50
	HSK63A-EMH25C-110	P2563029	25	65	110	59	24	25	M18	2	2.30
	HSK63A-EMH32C-110	P2563030	32	72	110	63	24	28	M20	2	2.60
	HSK100A-EMH6C-80	P2563059	6	25	80	35	18	-	M6	1	0.80
	HSK100A-EMH8C-80	P2563060	8	28	80	35	18	-	M8	1	0.80
100A	HSK100A-EMH10C-80	P2563052	10	35	80	35.5	20	-	M10	1	0.90
	HSK100A-EMH12C-80	P2563053	12	42	80	49	22.5	-	M12	1	1.10
	HSK100A-EMH14C-80	P2563054	14	44	80	49	22.5	-	M12	1	1.20
	HSK100A-EMH16C-100	P2563055	16	48	100	52	24	-	M14	1	1.30
	HSK100A-EMH18C-100	P2563056	18	50	100	52	24	-	M14	1	1.40
	HSK100A-EMH20C-100	P2563057	20	52	100	53	25	-	M16	1	1.50
	HSK100A-EMH25C-100	P2563058	25	65	100	59	24	25	M18	2	2.30
	HSK100A-EMH32C-100	P2772801	32	72	100	63	24	28	M20	2	2.60
	HSK100A-EMH40C-120	P2772802	40	80	120	73	30	32	M20	2	2.60

► Inch type products are available.

► Standard End Mill Holder is for a cutting tool with weldon shank and End Mill Holder for a cutting tool with Whistle notch is available upon request.

► Combi-style Holder with ball jointed clamping screw which can be used with cutting tools with Weldon and Whistle notch shank is available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

D187

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

TOOLING SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL HOLDER SET

BORING SYSTEM

ACCESSORY & PARTS

YG

END MILL HOLDER

EMH

END MILL HOLDER

FRÄSERFUTTER UND FLÄCHENSPANNFUTTER
MANDRIN PORTE FRAISE À QUEUE CYLINDRIQUE, À MÉPLAT
MANDRINI PORTA FRESA TIPO WELDON
PORTAFRESAS Y EJES DE SUJECCION LATERAL

HSK-A



FIG.1

FIG.2

DIN 69893-HSK

6.3G

15,000 RPM

AD

Unit : mm											
TAPER No.	MODEL No.	EDP No.	d1	D2	L	L1	L2	L3	M	FIG.	WEIGHT (Kg)
40A	HSK40A-EMH6-60	P2775522	6	25	60	38	18	-	M6	1	0.30
	HSK40A-EMH8-60	P2775523	8	28	60	38	18	-	M8	1	0.30
	HSK40A-EMH10-60	P2775524	10	35	60	42	20	-	M10	1	0.30
	HSK40A-EMH12-70	P2775525	12	42	70	47	22.5	-	M12	1	0.40
	HSK40A-EMH14-70	P2775526	14	44	70	47	22.5	-	M12	1	0.40
	HSK40A-EMH16-80	P2775527	16	48	80	50	24	-	M14	1	0.60
50A	HSK50A-EMH6-65	P2775528	6	25	65	38	18	-	M6	1	0.70
	HSK50A-EMH8-65	P2775529	8	28	65	38	18	-	M8	1	0.80
	HSK50A-EMH10-65	P2775530	10	35	65	42	20	-	M10	1	0.80
	HSK50A-EMH12-80	P2775531	12	42	80	47	22.5	-	M12	1	1.20
	HSK50A-EMH14-80	P2775532	14	44	80	47	22.5	-	M12	1	1.30
	HSK50A-EMH16-80	P2775533	16	48	80	50	24	-	M14	1	1.30
	HSK50A-EMH18-80	P2775534	18	50	80	50	24	-	M14	1	1.40
	HSK50A-EMH20-80	P2775535	20	52	80	52	25	-	M16	1	1.50
63A	HSK63A-EMH6-65	P2775501	6	25	65	35	18	-	M6	1	0.80
	HSK63A-EMH8-65	P2775502	8	28	65	38	18	-	M8	1	0.80
	HSK63A-EMH10-65	P2775503	10	35	65	42	20	-	M10	1	0.90
	HSK63A-EMH12-80	P2775504	12	42	80	47	22.5	-	M12	1	1.10
	HSK63A-EMH14-80	P2775505	14	44	80	47	22.5	-	M12	1	1.20
	HSK63A-EMH16-80	P2775506	16	48	80	50	24	-	M14	1	1.30
	HSK63A-EMH18-80	P2775507	18	50	80	50	24	-	M14	1	1.40
	HSK63A-EMH20-80	P2775508	20	52	80	52	25	-	M16	1	1.50
	HSK63A-EMH25-110	P2775509	25	65	110	60	24	25	M18	2	2.30
	HSK63A-EMH32-110	P2775510	32	72	110	64	24	28	M20	2	2.60
100A	HSK100A-EMH6-80	P2775511	6	25	80	35	18	-	M6	1	0.80
	HSK100A-EMH8-80	P2775512	8	28	80	35	18	-	M8	1	0.80
	HSK100A-EMH10-80	P2775513	10	35	80	39	20	-	M10	1	0.90
	HSK100A-EMH12-80	P2775514	12	42	80	47	22.5	-	M12	1	1.10
	HSK100A-EMH14-80	P2775515	14	44	80	47	22.5	-	M12	1	1.20
	HSK100A-EMH16-100	P2775516	16	48	100	50	24	-	M14	1	1.30
	HSK100A-EMH18-100	P2775517	18	50	100	50	24	-	M14	1	1.40
	HSK100A-EMH20-100	P2775518	20	52	100	52	25	-	M16	1	1.50
	HSK100A-EMH25-100	P2775519	25	65	100	60	24	25	M18	2	2.30
	HSK100A-EMH32-100	P2775520	32	72	100	64	24	28	M20	2	2.60
	HSK100A-EMH40-120	P2775521	40	80	120	74	30	32	M20	2	2.60

► Inch type products are available.

► Standard End Mill Holder is for a cutting tool with weldon shank and End Mill Holder for a cutting tool with Whistle notch is available upon request.

► Combi-style Holder with ball jointed clamping screw which can be used with cutting tools with Weldon and Whistle notch shank is available.

D188

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG

YG-1 CO., LTD.

TOOLING SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL HOLDER SET

BORING SYSTEM

ACCESSORY & PARTS

YG

END MILL HOLDER

EMH

END MILL HOLDER (COOLANT CHANNEL)

FRÄSERFUTTER UND FLÄCHENSPANNFUTTER
MANDRIN PORTE FRAISE À QUEUE CYLINDRIQUE, À MÉPLAT
MANDRINI PORTA FRESA TIPO WELDON
PORTAFRESAS Y EJES DE SUJECCION LATERAL

HSK-A



FIG.1

FIG.2

DIN 69893-HSK

6.3G

15,000 RPM

AD+C

Unit : mm											
TAPER No.	MODEL No.	EDP No.	d1	D2	L	L1	L2	L3	M	FIG.	WEIGHT (Kg)
40A	HSK40A-EMH6C-60	P2777222	6	25	60	38	18	-	M6	1	0.30
	HSK40A-EMH8C-60	P2777223	8	28	60	38	18	-	M8	1	0.30
	HSK40A-EMH10C-60	P2777224	10	35	60	42	20	-	M10	1	0.30
	HSK40A-EMH12C-70	P2777225	12	42	70	47	22.5	-	M12	1	0.40
	HSK40A-EMH14C-70	P2777226	14	44	70	47	22.5	-	M12	1	0.40
	HSK40A-EMH16C-80	P2777227	16	48	80	50	24	-	M14	1	0.60
50A	HSK50A-EMH6C-65	P2777228	6	25	65	38	18	-	M6	1	0.70
	HSK50A-EMH8C-65	P2777229	8	28	65	38	18	-	M8	1	0.80
	HSK50A-EMH10C-65	P2777230	10	35	65	42	20	-	M10	1	0.80
	HSK50A-EMH12C-80	P2777231	12	42	80	47	22.5	-	M12	1	1.20
	HSK50A-EMH14C-80	P2777232	14	44	80	47	22.5	-	M12	1	1.30
	HSK50A-EMH16C-80	P2777233	16	48	80	50	24	-	M14	1	1.30
	HSK50A-EMH18C-80	P2777234	18	50	80	50	24	-	M14	1	1.40
	HSK50A-EMH20C-80	P2777235	20	52	80	52	25	-	M16	1	1.50
	HSK63A-EMH6C-65	P2777201	6	25	65	35	18	-	M6	1	0.80
	HSK63A-EMH8C-65	P2777202	8	28	65	38	18	-	M8	1	0.80
63A	HSK63A-EMH10C-65	P2777203	10	35	65	42	20	-	M10	1	0.90
	HSK63A-EMH12C-80	P2777204	12	42	80	47	22.5	-	M12	1	1.10
	HSK63A-EMH14C-80	P2777206	14	44	80	47	22.5	-	M12	1	1.20
	HSK63A-EMH16C-80	P2777205	16	48	80	50	24	-	M14	1	1.30
	HSK63A-EMH18C-80	P2777207	18	50	80	50	24	-	M14	1	1.40
	HSK63A-EMH20C-80	P2777208	20	52	80	52	25	-	M16	1	1.50
	HSK63A-EMH25C-110	P2777209	25	65	110	60	24	25	M18	2	2.30
	HSK63A-EMH32C-110	P2777210	32	72	110	64	24	28	M20	2	2.60
	HSK100A-EMH6C-80	P2777211	6	25	80	35	18	-	M6	1	0.80
	HSK100A-EMH8C-80	P2777212	8	28	80	35	18	-	M8	1	0.80
	HSK100A-EMH10C-80	P2777213	10	35	80	35.5	20	-	M10	1	0.90
	HSK100A-EMH12C-80	P2777214	12	42	80	49	22.5	-	M12	1	1.10
100A	HSK100A-EMH14C-80	P2777215	14	44	80	49	22.5	-	M12	1	1.20
	HSK100A-EMH16C-100	P2777216	16	48	100	52	24	-	M14	1	1.30
	HSK100A-EMH18C-100	P2777217	18	50	100	52	24	-	M14	1	1.40
	HSK100A-EMH20C-100	P2777218	20	52	100	53	25	-	M16	1	1.50
	HSK100A-EMH25C-100	P2777219	25	65	100	59	24	25	M18	2	2.30
	HSK100A-EMH32C-100	P2777220	32	72	100	63	24	28	M20	2	2.60
	HSK100A-EMH40C-120	P2777221	40	80	120	73	30	32	M20	2	2.60

► Inch type products are available.

► Standard End Mill Holder is for a cutting tool with weldon shank and End Mill Holder for a cutting tool with Whistle notch is available upon request.

► Combi-style Holder with ball jointed clamping screw which can be used with cutting tools with Weldon and Whistle notch shank is available.

D189

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG

YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




SHELL MILL
ARBOR

SMA

SHELL MILL ARBOR

AUFNAHMEDORN FÜR FRÄSER MIT BOHRUNG
MANDRIN PORTE-FRAISES
MANDRINO CON TRASCINAMENTO FISSO
PORTA FRESAS

HSK-A



DIN
69893-
HSK

6.3G

15,000
RPM

AD

Unit : mm								
TAPER No.	MODEL No.	EDP No.	D1	D2	L	H	BOLT	WEIGHT (Kg)
40A	HSK40A-SMA16-50	P2778201	16	32	50	17	M8x16L	0.40
	HSK40A-SMA22-50	P2778202	22	40	50	19	M10x18L	0.50
	HSK40A-SMA27-60	P2778203	27	48	60	21	M12x22L	0.60
50A	HSK50A-SMA16-50	P2778204	16	32	50	17	M8x16L	0.50
	HSK50A-SMA22-60	P2778205	22	40	60	19	M10x18L	0.57
	HSK50A-SMA27-60	P2778206	27	48	60	21	M12x22L	0.75
	HSK50A-SMA32-60	P2778207	32	58	60	24	M16x26L	0.90
63A	HSK63A-SMA16-50	P2566001	16	32	50	17	M8x16L	0.81
	HSK63A-SMA22-50	P2566002	22	40	50	19	M10x18L	0.93
	HSK63A-SMA27-60	P2566003	27	48	60	21	M12x22L	1.22
	HSK63A-SMA32-60	P2566004	32	58	60	24	M16x26L	1.46
	HSK63A-SMA40-60	P2566005	40	70	60	27	M20x30L	1.80
100A	HSK100A-SMA16-50	P2566011	16	32	50	17	M8x16L	2.14
	HSK100A-SMA22-50	P2566012	22	40	50	19	M10x18L	2.25
	HSK100A-SMA27-50	P2566013	27	48	50	21	M12x22L	2.40
	HSK100A-SMA32-50	P2566014	32	58	50	24	M16x26L	2.60
	HSK100A-SMA40-60	P2566015	40	70	60	27	M20x30L	3.25
	HSK100A-SMA50-70	P2778209	50	90	70	30	M24x36L	5.40

► Inch type products are available.

► For parts, please refer to page D311.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




SHELL MILL
ARBOR

SMA

SHELL MILL ARBOR (COOLANT CHANNEL & SMALL FACE)

AUFNAHMEDORN FÜR FRÄSER MIT BOHRUNG
MANDRIN PORTE-FRAISES
MANDRINO CON TRASCINAMENTO FISSO
PORTA FRESAS

HSK-A



DIN
69893-
HSK

6.3G

15,000
RPM

AD+C

Unit : mm								
TAPER No.	MODEL No.	EDP No.	D1	D2	L	H	BOLT	WEIGHT (Kg)
63A	HSK63A-SMA16C-50	P2566001C	16	32	50	17	M8x16L	0.80
	HSK63A-SMA22C-50	P2566002C	22	40	50	19	M10x18L	0.92
	HSK63A-SMA22C-100	P2801101C	22	40	100	19	M10x18L	1.40
	HSK63A-SMA22C-160	P2803202C	22	40	160	19	M10x18L	1.97
	HSK63A-SMA27C-60	P2566003C	27	48	60	21	M12x22L	1.19
	HSK63A-SMA27C-100	P2801102C	27	48	100	21	M12x22L	1.74
	HSK63A-SMA27C-160	P2803204C	27	48	160	21	M12x22L	2.55
	HSK63A-SMA32C-60	P2566004C	32	58	60	24	M16x26L	1.50
	HSK63A-SMA32C-100	P2801103C	32	58	100	24	M16x26L	2.72
	HSK63A-SMA40C-60	P2566005C	40	70	60	27	M20x30L	1.66
	HSK100A-SMA16C-50	P2566011C	16	32	50	17	M8x16L	2.25
100A	HSK100A-SMA22C-50	P2566012C	22	40	50	19	M10x18L	2.25
	HSK100A-SMA22C-100	P2801105C	22	40	100	19	M10x18L	2.72
	HSK100A-SMA22C-160	P2803206C	22	40	160	19	M10x18L	3.28
	HSK100A-SMA27C-50	P2566013C	27	48	50	21	M12x22L	2.40
	HSK100A-SMA27C-100	P2801106C	27	48	100	21	M12x22L	3.12
	HSK100A-SMA27C-160	P2803207C	27	48	160	21	M12x22L	4.01
	HSK100A-SMA32C-50	P2566014C	32	58	50	24	M16x26L	2.55
	HSK100A-SMA32C-100	P2801107C	32	58	100	24	M16x26L	3.49
	HSK100A-SMA32C-160	P2803208C	32	58	160	24	M16x26L	4.66
	HSK100A-SMA40C-60	P2566015C	40	70	60	27	M20x30L	3.10
	HSK100A-SMA40C-100	P2801108C	40	70	100	27	M20x30L	4.19
	HSK100A-SMA40C-160	P2803209C	40	70	160	27	M20x30L	5.88

► Inch type products are available.

► With "Coolant Through" by coolant channels.

► For parts, please refer to page D311.

D190

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

D191

TOOLING SYSTEM

SK (DIN 69871)

CBT (BT DUAL CONTACT)

BT (JIS B6339/ MAS 403)

HSK (DIN 69893/ ISO 12164)

STRAIGHT

ISO, NT, MTA/MTB, GOST

TOOL HOLDER SET

BORING SYSTEM

ACCESSORY & PARTS



SHELL MILL ARBOR


SMA

SHELL MILL ARBOR (COOLANT CHANNEL & LARGE FACE)

AUFNAHMEDORN FÜR FRÄSER MIT BOHRUNG
MANDRIN PORTE-FRAISES
MANDRINO CON TRASCINAMENTO FISSO
PORTA FRESAS

HSK-A





DIN 69893-HSK

6.3G

15,000 RPM

AD+C

Unit : mm								
TAPER No.	MODEL No.	EDP No.	D1	D2	L	H	BOLT	WEIGHT (Kg)
63A	HSK63A-SMA16CE-50	P2803301CE	16	38	50	17	M8x16L	0.86
	HSK63A-SMA16CE-100	P2803302CE	16	38	100	17	M8x16L	1.29
	HSK63A-SMA16CE-145	P2803303CE	16	38	145	17	M8x16L	1.68
	HSK63A-SMA22CE-50	P2803304CE	22	48	50	19	M10x18L	1.02
	HSK63A-SMA22CE-100	P2803305CE	22	48	100	19	M10x18L	1.71
	HSK63A-SMA22CE-160	P2803306CE	22	48	160	19	M10x18L	2.54
	HSK63A-SMA27CE-60	P2803307CE	27	60	60	21	M12x22L	1.39
	HSK63A-SMA27CE-100	P2803308CE	27	60	100	21	M12x22L	2.25
	HSK63A-SMA27CE-160	P2803309CE	27	60	160	21	M12x22L	3.54
	HSK63A-SMA32CE-60	P2803310CE	32	78	60	24	M16x26L	1.70
	HSK63A-SMA32CE-100	P2803311CE	32	78	100	24	M16x26L	3.40
100A	HSK63A-SMA40CE-60	P2803312CE	40	89	60	27	M20x30L	1.99
	HSK100A-SMA16CE-100	P2803313CE	16	38	100	17	M8x16L	2.63
	HSK100A-SMA22CE-50	P2803314CE	22	48	50	19	M10x18L	2.34
	HSK100A-SMA22CE-100	P2803315CE	22	48	100	19	M10x18L	3.02
	HSK100A-SMA22CE-160	P2803316CE	22	48	160	19	M10x18L	3.85
	HSK100A-SMA27CE-50	P2803317CE	27	60	50	21	M12x22L	2.54
	HSK100A-SMA27CE-100	P2803318CE	27	60	100	21	M12x22L	3.60
	HSK100A-SMA27CE-160	P2803319CE	27	60	160	21	M12x22L	4.90
	HSK100A-SMA32CE-50	P2803320CE	32	78	50	24	M16x26L	2.90
	HSK100A-SMA32CE-100	P2803321CE	32	78	100	24	M16x26L	4.68
	HSK100A-SMA32CE-160	P2803322CE	32	78	160	24	M16x26L	6.86
	HSK100A-SMA40CE-60	P2803323CE	40	89	60	27	M20x30L	3.68
	HSK100A-SMA40CE-100	P2803324CE	40	89	100	27	M20x30L	5.51
	HSK100A-SMA40CE-160	P2803325CE	40	89	160	27	M20x30L	8.32

► Inch type products are available.

► With "Coolant Through" by coolant channels.

► For parts, please refer to page D311.

D192

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING SYSTEM

SK (DIN 69871)

CBT (BT DUAL CONTACT)

BT (JIS B6339/ MAS 403)

HSK (DIN 69893/ ISO 12164)

STRAIGHT

ISO, NT, MTA/MTB, GOST

TOOL HOLDER SET

BORING SYSTEM

ACCESSORY & PARTS




SHELL MILL ARBOR


SMF

SHELL MILL ARBOR (FLANGE MOUNTING)

AUFNAHMEDORN FÜR FRÄSER MIT BOHRUNG
MANDRIN PORTE-FRAISES
MANDRINO CON TRASCINAMENTO FISSO
PORTA FRESAS

HSK-A





DIN 69893-HSK

6.3G

15,000 RPM

AD

Unit : mm											
TAPER No.	MODEL No.	EDP No.	d	D1	D2	D3	L	H1	M (TAP)	DRIVE KEY & BOLT	WEIGHT (Kg)
100A	HSK100A-SMF60-75	P2524025	14	60	129	101.6	75	40	4-M16	25.4 x 25.4 x 31.5, M12-25L	-

► Inch type products are available.

D193

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET


BORING
SYSTEM


ACCESSORY
& PARTS



COMBI-SHELL
MILL ARBOR

CMA





HSK-A



6.3G





Unit : mm								
TAPER No.	MODEL No.	EDP No.	d	L	D	H1	H	WEIGHT (Kg)
50A	HSK50A-CMA16-50	P2562006	16	50	32	17	27	0.56
	HSK50A-CMA22-50	P2562007	22	50	40	19	31	0.66
	HSK50A-CMA27-65	P2562008	27	65	48	21	33	0.96
	HSK50A-CMA32-65	P2562009	32	65	58	24	38	1.15
63A	HSK63A-CMA16-60	P2562001	16	60	32	17	27	0.88
	HSK63A-CMA22-60	P2562002	22	60	40	19	31	1.02
	HSK63A-CMA27-60	P2562003	27	60	48	21	33	1.20
	HSK63A-CMA32-60	P2562004	32	60	53	24	38	1.43
	HSK63A-CMA40-70	P2562005	40	70	70	27	41	1.93
100A	HSK100A-CMA16-60	P2562011	16	60	32	17	27	2.22
	HSK100A-CMA22-60	P2562012	22	60	40	19	31	2.34
	HSK100A-CMA27-60	P2562013	27	60	48	21	33	2.56
	HSK100A-CMA32-60	P2562014	32	60	58	24	38	2.69
	HSK100A-CMA40-70	P2562015	40	70	70	27	41	3.39
	HSK100A-CMA50-80	P2562010	50	80	90	30	46	4.50

► Inch type products are available.

► For parts, please refer to page D312.

D194

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM


ACCESSORY
& PARTS



POWER MILLING
CHUCK

C





HSK-A



6.3G





Unit : mm							
TAPER No.	MODEL No.	EDP No.	d1	D1	L	H	WEIGHT (Kg)
50A	HSK50A-C20-100HS	P2773102	20	54	100	70	1.30
63A	HSK63A-C20-105HS	P2562016	20	54	105	70	1.50
	HSK63A-C25-120HS	P2773103	25	62	120	80	2.20
	HSK63A-C32-130HS	P2562017	32	72	130	100	2.70
100A	HSK100A-C20-110HS	P2773104	20	54	110	70	3.50
	HSK100A-C25-130HS	P2773105	25	62	130	80	3.80
	HSK100A-C32-135HS	P2773101	32	72	135	100	4.20
	HSK100A-C42-135HS	P2773106	42	72	135	100	5.30

► Inch type products are available.

► Balancing Grade is adjusted on Basic holder only without Clamping Cap.

► For applicable collet and spanner, please refer to the page D314.

D195

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




SK SLIM
CHUCK

SKA

SK SLIM CHUCK

SK SCHLANKE FUTTER
MANDRIN TYPE SK MINCE
SK MANDRINI SOTTILI
PORTAHERRAMIENTAS SK EJE REDUCIDO





DIN
69893-
HSK

2.5G

25,000
RPM

AD

Unit : mm									
TAPER No.	MODEL No.	EDP No.	CLAMPING RANGE	L	D	D1	H	COLLET	WEIGHT (Kg)
32A	HSK32A-SKA06-50	P2775860	1.8 - 6.0	50	20	19.5	31	SKC6	0.50
	HSK32A-SKA10-60	P2775861	1.75 - 10.0	60	28	26	35	SKC10	0.70
40A	HSK40A-SKA06-60	P2775862	1.8 - 6.0	60	20	19.5	31	SKC6	0.70
	HSK40A-SKA10-60	P2775863	1.75 - 10.0	60	28	27.5	35	SKC10	0.90
	HSK40A-SKA13-80	P2775864	2.75 - 13.0	80	33	33	43.6	SKC13	1.00
50A	HSK50A-SKA06-80	P2775865	1.8 - 6.0	80	20	19.5	31	SKC6	0.90
	HSK50A-SKA10-100	P2775866	1.75 - 10.0	100	28	27.5	35	SKC10	1.10
	HSK50A-SKA13-100	P2775867	2.75 - 13.0	100	33	33	43.6	SKC13	1.20
63A	HSK63A-SKA06-100	P2775868	1.8 - 6.0	100	20	19.5	31	SKC6	1.40
	HSK63A-SKA10-100	P2775869	1.75 - 10.0	100	28	27.5	35	SKC10	1.60
	HSK63A-SKA13-100	P2775870	2.75 - 13.0	100	33	33	43.6	SKC13	1.70
	HSK63A-SKA16-120	P2775871	2.75 - 16.0	120	40	40	52	SKC16	1.70
	HSK63A-SKA20-120	P2775872	3.5 - 20.0	120	48.5	48.5	59.6	SKC20	2.10
	HSK63A-SKA25-150	P2775873	16.0 - 25.4	150	55	55	63.4	SKC25	2.40
80A	HSK80A-SKA06-120	P2775893	1.8 - 6.0	120	20	19.5	31	SKC6	1.60
	HSK80A-SKA10-120	P2775875	1.75 - 10.0	120	28	27.5	35	SKC10	1.72
	HSK80A-SKA13-120	P2775876	2.75 - 13.0	120	33	33	43.6	SKC13	1.79
	HSK80A-SKA16-120	P2775877	2.75 - 16.0	120	40	40	52	SKC16	1.96
	HSK80A-SKA20-130	P2775878	3.5 - 20.0	130	48.5	48.5	59.6	SKC20	2.39
	HSK80A-SKA25-150	P2775879	16.0 - 25.4	150	55	55	63.4	SKC25	2.82
100A	HSK100A-SKA06-120	P2775880	1.8 - 6.0	120	20	19.5	31	SKC6	4.00
	HSK100A-SKA10-150	P2775881	1.75 - 10.0	150	28	27.5	35	SKC10	4.50
	HSK100A-SKA13-150	P2775882	2.75 - 13.0	150	33	33	43.6	SKC13	4.60
	HSK100A-SKA16-150	P2775883	2.75 - 16.0	150	40	40	52	SKC16	5.10
	HSK100A-SKA20-150	P2775884	3.5 - 20.0	150	48.5	48.5	59.6	SKC20	5.40
	HSK100A-SKA25-160	P2775885	16.0 - 25.4	160	55	55	63.4	SKC25	5.50

► Inch type products are available.

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

► For applicable Collet, Nut and Spanner, please refer to page D315~D317.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




SK SLIM
CHUCK

SKA

SK SLIM CHUCK

SK SCHLANKE FUTTER
MANDRIN TYPE SK MINCE
SK MANDRINI SOTTILI
PORTAHERRAMIENTAS SK EJE REDUCIDO





DIN
69893-
HSK

6.3G

15,000
RPM

AD

Unit : mm									
TAPER No.	MODEL No.	EDP No.	CLAMPING RANGE	L	D	D1	H	COLLET	WEIGHT (Kg)
32A	HSK32A-SKA06-50	P2775860	1.8 - 6.0	50	20	19.5	31	SKC6	0.50
	HSK32A-SKA10-60	P2775861	1.75 - 10.0	60	28	26	35	SKC10	0.70
40A	HSK40A-SKA06-60	P2775862	1.8 - 6.0	60	20	19.5	31	SKC6	0.70
	HSK40A-SKA10-60	P2775863	1.75 - 10.0	60	28	27.5	35	SKC10	0.90
	HSK40A-SKA13-80	P2775864	2.75 - 13.0	80	33	33	43.6	SKC13	1.00
50A	HSK50A-SKA06-80	P2775865	1.8 - 6.0	80	20	19.5	31	SKC6	0.90
	HSK50A-SKA10-100	P2775866	1.75 - 10.0	100	28	27.5	35	SKC10	1.10
	HSK50A-SKA13-100	P2775867	2.75 - 13.0	100	33	33	43.6	SKC13	1.20
63A	HSK63A-SKA06-100	P2775868	1.8 - 6.0	100	20	19.5	31	SKC6	1.40
	HSK63A-SKA10-100	P2775869	1.75 - 10.0	100	28	27.5	35	SKC10	1.60
	HSK63A-SKA13-100	P2775870	2.75 - 13.0	100	33	33	43.6	SKC13	1.70
	HSK63A-SKA16-120	P2775871	2.75 - 16.0	120	40	40	52	SKC16	1.70
	HSK63A-SKA20-120	P2775872	3.5 - 20.0	120	48.5	48.5	59.6	SKC20	2.10
	HSK63A-SKA25-150	P2775873	16.0 - 25.4	150	55	55	63.4	SKC25	2.40
80A	HSK80A-SKA06-120	P2775893	1.8 - 6.0	120	20	19.5	31	SKC6	1.60
	HSK80A-SKA10-120	P2775875	1.75 - 10.0	120	28	27.5	35	SKC10	1.72
	HSK80A-SKA13-120	P2775876	2.75 - 13.0	120	33	33	43.6	SKC13	1.79
	HSK80A-SKA16-120	P2775877	2.75 - 16.0	120	40	40	52	SKC16	1.96
	HSK80A-SKA20-130	P2775878	3.5 - 20.0	130	48.5	48.5	59.6	SKC20	2.39
	HSK80A-SKA25-150	P2775879	16.0 - 25.4	150	55	55	63.4	SKC25	2.82
100A	HSK100A-SKA06-120	P2775880	1.8 - 6.0	120	20	19.5	31	SKC6	4.00
	HSK100A-SKA10-150	P2775881	1.75 - 10.0	150	28	27.5	35	SKC10	4.50
	HSK100A-SKA13-150	P2775882	2.75 - 13.0	150	33	33	43.6	SKC13	4.60
	HSK100A-SKA16-150	P2775883	2.75 - 16.0	150	40	40	52	SKC16	5.10
	HSK100A-SKA20-150	P2775884	3.5 - 20.0	150	48.5	48.5	59.6	SKC20	5.40
	HSK100A-SKA25-160	P2775885	16.0 - 25.4	160	55	55	63.4	SKC25	5.50

► Inch type products are available.

► For applicable Collet, Nut and Spanner, please refer to page D315~D317.

D198

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

D199

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS



SK SLIM
CHUCK


SKA

SK SLIM CHUCK

SK SCHLANKE FUTTER
MANDRIN TYPE SK MINCE
SK MANDRINI SOTTILI
PORTAHERRAMIENTAS SK EJE REDUCIDO

HSK-E





DIN
69893-
HSK

2.5G

25,000
RPM

AD

Unit : mm									
TAPER No.	MODEL No.	EDP No.	CLAMPING RANGE	L	D	D1	H	COLLET	WEIGHT (Kg)
25E	HSK25E-SKA06-45	P2775886	1.8 - 6.0	45	20	19.5	31	SKC6	0.12
	HSK25E-SKA10-50	P2775887	1.75 - 10.0	50	28	21.5	35	SKC10	0.14
32E	HSK32E-SKA06-50	P2775888	1.8 - 6.0	50	20	19.5	31	SKC6	0.50
	HSK32E-SKA10-60	P2775889	1.75 - 10.0	60	28	26	35	SKC10	0.70
40E	HSK40E-SKA06-60	P2775890	1.8 - 6.0	60	20	19.5	31	SKC6	0.70
	HSK40E-SKA10-60	P2775891	1.75 - 10.0	60	28	27.5	35	SKC10	0.90
	HSK40E-SKA13-80	P2775892	2.75 - 13.0	80	33	33	43.6	SKC13	1.00

► Balancing grade G2.5 at 25,000RPM or U max. < 1gmm.

DIN
69893-
HSK

6.3G

15,000
RPM

AD

Unit : mm									
TAPER No.	MODEL No.	EDP No.	CLAMPING RANGE	L	D	D1	H	COLLET	WEIGHT (Kg)
25E	HSK25E-SKA06-45	P2773523	1.8 - 6.0	45	20	19.5	31	SKC6	0.12
	HSK25E-SKA10-50	P2773524	1.75 - 10.0	50	28	21.5	35	SKC10	0.14
32E	HSK32E-SKA06-50	P2773525	1.8 - 6.0	50	20	19.5	31	SKC6	0.50
	HSK32E-SKA10-60	P2773526	1.75 - 10.0	60	28	26	35	SKC10	0.70
40E	HSK40E-SKA06-60	P2773527	1.8 - 6.0	60	20	19.5	31	SKC6	0.70
	HSK40E-SKA10-60	P2773528	1.75 - 10.0	60	28	27.5	35	SKC10	0.90
	HSK40E-SKA13-80	P2773529	2.75 - 13.0	80	33	33	43.6	SKC13	1.00

► Inch type products are available.
► For applicable Collet, Nut and Spanner, please refer to page D315~D317.

D200

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




SYNCHRO
TAPPING CHUCK


SYTER

SYNCHRO TAPPING CHUCK (ER TYPE)

SYNCHRO GEWINDESCHNEIDFUTTER (ER)
SYNCHRO TARAUDER (ER)
SINCRO MANDRINI PER MASCHIATURA (ER)
SINCRO PORTAMACHOS (ER)

HSK-A





DIN
69893-
HSK

AD

Unit : mm										
TAPER No.	MODEL No.	EDP No.	TAP SIZE	NUT/COLLET	D1	D2	L	L1	TENSION/ COMPRESSION	WEIGHT (Kg)
63A	HSK63A-SYTER12-105	P2773812	M3-M12	ER16	28	34	105	31	±0.2	-
	HSK63A-SYTER16-106	P2773808	M3-M16	ER20	34	34	106	31	±0.2	0.95
	HSK63A-SYTER16-120	P2773804	M3-M16	ER20	34	34	120	31	±0.2	-
	HSK63A-SYTER20-110	P2773809	M3-M20	ER25	42	34	110	37.5	±0.2	0.95
	HSK63A-SYTER20-120	P2773805	M3-M20	ER25	42	34	120	37.5	±0.2	-
	HSK63A-SYTER27-115	P2773810	M4-M27	ER32	50	45	115	41	±0.2	1.34
	HSK63A-SYTER27-155	P2773813	M4-M27	ER32	50	45	155	41	±0.2	-
	HSK63A-SYTER33-130	P2773814	M4-M33	ER40	63	62	130	60	±0.2	-
100A	HSK100A-SYTER20-106	P2773807	M3-M20	ER25	42	34	106	36	±0.2	0.95
	HSK100A-SYTER27-124	P2773815	M4-M27	ER32	50	45	124	41	±0.2	-
	HSK100A-SYTER27-155	P2773816	M4-M27	ER32	50	45	155	41	±0.2	-
	HSK100A-SYTER33-135	P2773817	M4-M33	ER40	63	62	135	60	±0.2	-

► Feature :
- Compensation for synchronization errors to extend tap life and to improve thread quality.
- To compensate for pitch tolerances of taps.
- For machine with synchronized spindle.
► Inch type products are available.
► ER collet of page D296~D302, and Tap ER collet of page D303~D304 are applicable.

D201

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS



SYNCHRO
TAPPING CHUCK


SYTC

SYNCHRO TAPPING CHUCK (QUICK CHANGE TYPE)

SYNCHRO GEWINDESCHNEID-SCHNELLWECHSELFUTTER
SYNCHRO TARAUDER À CHANGEMENT RAPIDE
SINCRO MANDRINO PER MASCHIARE
SINCRO PORTAMACHOS DE CAMBIO RAPIDO

HSK-A





DIN
69893-
HSK



Unit : mm									
TAPER No.	MODEL No.	EDP No.	TAP SIZE	TAP ADAPTOR	d1	D1	L	L1	WEIGHT (Kg)
32A	HSK32A-SYTC12-75	P2774314	M3-M12	TCS12	19	36	75	55	0.32
50A	HSK50A-SYTC12-72	P2774315	M3-M12	TCS12	19	36	72	46	0.54
	HSK50A-SYTC20-91	P2774316	M6-M24	TCS24	31	50	91	65	0.70
63A	HSK63A-SYTC12-75	P2774301	M3-M12	TCS12	19	36	75	49	0.82
	HSK63A-SYTC12-80	P2774302	M3-M12	TCS12	19	36	80	54	0.85
	HSK63A-SYTC12-120	P2774303	M3-M12	TCS12	19	36	120	94	1.08
	HSK63A-SYTC12-152	P2774304	M3-M12	TCS12	19	36	152	126	1.27
	HSK63A-SYTC12-180	P2774305	M3-M12	TCS12	19	36	180	154	1.44
	HSK63A-SYTC20-89	P2774306	M6-M24	TCS24	31	50	89	63	0.84
	HSK63A-SYTC33-121	P2774307	M18-M38	TCS38	48	74	121	95	1.45
	HSK100A-SYTC12-75	P2774308	M3-M12	TCS12	19	36	75	43	2.20
	HSK100A-SYTC12-160	P2774309	M3-M12	TCS12	19	36	160	131	2.60
100A	HSK100A-SYTC20-94	P2774310	M6-M24	TCS24	31	50	94	65	2.39
	HSK100A-SYTC20-160	P2774311	M6-M24	TCS24	31	50	160	131	2.99
	HSK100A-SYTC33-127	P2774312	M18-M38	TCS38	48	74	127	98	3.11
	HSK100A-SYTC33-160	P2774313	M18-M38	TCS38	48	74	160	131	4.03

► Feature :

- Compensation for synchronization errors to extend tap life and to improve thread quality.

- To compensate for pitch tolerances of taps.

- For machine with synchronized spindle.

► For applicable Tap Adaptor, please refer to page D318~D319.

D202

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS




ONE STEP
TAPPING CHUCK


OTC

ONE STEP TAPPING CHUCK

GEWINDE-SCHNELLWECHSELFUTTER
MANDRIN DE TARAUDAGE À CHANGEMENT RAPIDE
PORTAMASCHI A CAMBIO RAPIDO
MANDRINO DE CAMBIO RÁPIDO CON ROSCA

HSK-A





DIN
69893-
HSK



Unit : mm									
TAPER No.	MODEL No.	EDP No.	d1	D2	L1	L2	LENGTH COMPENSATION		WEIGHT (Kg)
							Compression	Tension	
63A	HSK63A-OTC-M3-M12-77	P2802401	19	36	77	51	7.5	7.5	1.10
	HSK63A-OTC-M8-M20-110	P2802402	31	53	110	84	12.5	12.5	1.50
	HSK63A-OTC-M14-M36-155	P2802403	48	78	155	129	20	20	3.30
100A	HSK100A-OTC-M3-M12-85.5	P2802404	19	36	85.5	56.5	7.5	7.5	3.00
	HSK100A-OTC-M8-M20-119.5	P2802405	31	53	119.5	90.5	12.5	12.5	3.30
	HSK100A-OTC-M14-M36-161	P2802406	48	78	161	132	20	20	5.20

► For applicable Tap Adaptor, please refer to page D318~D319.

D203

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS



TAPPING ER
CHUCK


TER

HSK-A

TAPPING ER CHUCK

ER - GEWINDESCHNEIDFUTTER
MANDRIN DE TARAUDAGE PINCE ER
MANDRINI PORTAPINZA ER PER MASCHIATURA
PORTAPINZAS ER PARA MACHOS





DIN
69893-
HSK



Unit : mm									
TAPER No.	MODEL No.	EDP No.	D	D1	D2	L	L1	NUT / COLLET	WEIGHT (Kg)
50A	HSK50A-TER16-125	P2774107	28	41	45	125	93.4	ER16	1.20
	HSK50A-TER16-150	P2774108	28	41	45	150	118.4	ER16	1.30
63A	HSK63A-TER16-125	P2774101	28	41	45	125	93.4	ER16	1.70
	HSK63A-TER16-150	P2774102	28	41	45	150	118.4	ER16	1.85
	HSK63A-TER32-150	P2774103	50	58	63	150	112	ER32	2.10
	HSK63A-TER32-180	P2774109	50	58	63	180	142	ER32	2.30
100A	HSK100A-TER16-130	P2774104	28	41	45	130	98.4	ER16	4.00
	HSK100A-TER16-150	P2774105	28	41	45	150	118.4	ER16	4.20
	HSK100A-TER32-150	P2774106	50	58	63	150	112	ER32	4.40
	HSK100A-TER32-180	P2774110	50	58	63	180	142	ER32	4.60

► Inch type products are available.

► ER collet of page D296~D302 and Tap ER collet of page D303~D304 are applicable.

D204

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

 YG-1 CO., LTD.

TOOLING
SYSTEM

SK
(DIN 69871)

CBT
(BT DUAL
CONTACT)

BT
(JIS B6339/
MAS 403)

HSK
(DIN 69893/
ISO 12164)

STRAIGHT

ISO, NT,
MTA/MTB,
GOST

TOOL
HOLDER
SET

BORING
SYSTEM

ACCESSORY
& PARTS



TAPPING
CHUCK


TC

HSK-A

TAPPING CHUCK

GEWINDESCHNEID - SCHNELLWECHSELFUTTER
TARAUDER À CHANGEMENT RAPIDE
MANDRINO PER MASCHIARE
PORTAMACHOS DE CAMBIO RAPIDO





DIN
69893-
HSK



Unit : mm										
TAPER No.	MODEL No.	EDP No.	TAP SIZE	TAP ADAPTOR	LENGTH COMPENSATION		d1	D1	L	WEIGHT (Kg)
					Compression	Tension				
50A	HSK50A-TC12-120	P2774506	M3-M12	TCS12	5	15	19	45	120	0.80
	HSK63A-TC12-120	P2774501	M3-M12	TCS12	5	15	19	45	120	1.00
63A	HSK63A-TC12-150	P2774507	M3-M12	TCS12	5	15	19	45	150	1.70
	HSK63A-TC24-142	P2774502	M6-M24	TCS24	5	20	31	63	142	2.40
	HSK63A-TC24-172	P2774508	M6-M24	TCS24	5	20	31	63	172	2.70
	HSK100A-TC12-130	P2774503	M3-M12	TCS12	5	15	19	45	130	4.30
100A	HSK100A-TC12-175	P2774509	M3-M12	TCS12	5	15	19	45	175	4.80
	HSK100A-TC12-220	P2774510	M3-M12	TCS12	5	15	19	45	220	5.30
	HSK100A-TC24-142	P2774504	M6-M24	TCS24	5	20	31	63	142	5.20
	HSK100A-TC24-187	P2774511	M6-M24	TCS24	5	20	31	63	187	6.60
	HSK100A-TC38-200	P2774505	M18-M38	TCS38	10	25	48	98	200	8.00

► For applicable Tap Adaptor, please refer to page D318~D319.

 YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

D205


YG BLANK
BAR

BL

BLANK BAR

BOHRSTANGENROHLING
EBAUCHE DE BARRES D ALÉSAGE
BARRA ALESATRICE GREZZA
PIEZA EN BRUTO PARA BARRAS DE MANDRINAR

HSK-A



Unit : mm					
TAPER No.	MODEL No.	EDP No.	D	L	WEIGHT(Kg)
63A	HSK63A-BL63-160	P2779198	63	160	3.91
100A	HSK100A-BL97-250	P2779199	97	250	17.70


YG TEST
BAR

TB

TEST BAR

KONTROLLDORN
MANDRIN DE CONTRÔLE
MANDRINO DI CONTROLLO
MANDRIL DE CONTROL

HSK-A



Unit : mm					
TAPER No.	MODEL No.	EDP No.	D	L	WEIGHT(Kg)
63A	HSK63A-TB40-300	P2802303	40	300	2.90
100A	HSK100A-TB50-300	P2802304	50	300	6.17

YG-1 TOOLING SYSTEM

STRAIGHT



SHRINK FIT HOLDER - EXTENSION

ER COLLET CHUCK

SK SLIM CHUCK

SYNCHRO TAPPING CHUCK

ONE STEP TAPPING CHUCK

TAPPING CHUCK

NC DRILL CHUCK (KEYLESS TYPE)